



**THE ULTIMATE  
CHOICE  
FOR  
SAFETY  
SHOES.**

**DATA SHEET**



# NITRILE

## 2001 H

- Nitrile Rubber
- Steel Safety Toe
- Heat Resistant (Up to 300 C)
- Chemical Resistant Outsole



Brand	CHEETAH
Product Line	Nitrile
Description	Low Cut Lace Up Shoes
Sizes	4 – 12 ( UK )
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Insock	AIRGO PU™ Comfort Insole
Weight (Approx. Size 7)	594 grams

### Upper Material

Apron	Full Grain Buffalo Leather 1.8-2.0 Black
Vamp In	Full Grain Buffalo Leather 1.8-2.0 Black
Vamp Out	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter IN	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter Out	Full Grain Buffalo Leather 1.8-2.0 Black
Back counter	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter Label	Cheetah Tab TPR Red

### Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Black Polyester Mesh
Collar Lining	Black Polyester Mesh

<b>Standard Compliance</b>	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 22.08 mm (> 14mm Std)
Toe Compression 1500 N	Clearance 23.26 mm (>14mm Std)

### Miscellaneous

Collar Padding	24 mm Foam Density 30
Inner counter	Thermoplastic heel counter
Thread	Thread Bonded Nylon

### Outsole

Material	Nitrile
Hardness	65 - 70 Shore A
Antistatic	16.6 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	300°C



Steel toe protects from impact and compression



Strong and durable nitrile rubber outsole



Heat resistant up to 300 C



Acid and alkali resistant soles



PU Insole improves heel cushioning



# NITRILE

## 2002 H



- Nitrile Rubber
- Heat Resistant (Up to 300 C)
- Steel Safety Toe
- Chemical Resistant Outsole

Brand	Cheetah
Product Line	Nitrile
Description	Low Cut lace up shoes
Sizes	4 – 12 ( UK )
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Sole	Nitrile
Insock	AIRGO PU™ Comfort Insole
Weight (Approx. Size 7)	647 grams

### Upper Material

Vamp	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter In	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter Out	Full Grain Buffalo Leather 1.8-2.0 Black
Back counter	Full Grain Buffalo Leather 1.8-2.0 Black
Collar	Pvc R 38 Black Backing TPE 0.8 mm
Tongue	Pvc R 38 Black Backing TPE 0.8 mm
Collar Padding	24 mm Foam Density 30
Tongue Padding	8 mm Foam Density 30
Tongue Label	"Animal CHEETAH" Polyester Label
Quarter Label	Label Cheetah Tab TPR Red

### Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Mesh Black
Collar Lining	Mesh Black

<b>Standard Compliance</b>	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 22.08mm (> 14mm Std)
Toe Compression 1500 N	Clearance 23.26mm (>14mm Std)

### Miscellaneous

Eyelet	Hexagonal No washer Gunmetal
Lace	Round lace Black 90 Cm
Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

### Outsole

Material	Nitrile
Hardness	65 - 70 Shore A
Antistatic	16.6 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	300°C



Steel toe protects from impact and compression



Strong and durable nitrile rubber outsole



Heat resistant up to 300 C



Acid and alkali resistant soles



PU Insole improves heel cushioning



# NITRILE

## 2101 H

- Nitrile Rubber
- Heat Resistant (Up to 300 C)
- Steel Safety Toe
- Chemical Resistant Outsole



Brand	CHEETAH
Product Line	Nitrile
Description	Zip Up Ankle Boots with zipper
Sizes	4 – 12 ( UK )
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Insock	AIRGO PU™ Comfort Insole
Weight (Approx. Size 7)	620 grams

### Upper Material

Toe bumper	Full Grain Buffalo Leather 1.8-2.0 Black
Vamp	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter IN	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter Out	Full Grain Buffalo Leather 1.8-2.0 Black
Back counter	Full Grain Buffalo Leather 1.8-2.0 Black
Zipper Backing	Full Grain Buffalo Leather 1.8-2.0 Black
Collar	Pvc R 38 Black Backing TPE 0.8 mm

### Lining

Vamp Lining	Grey polyester Non Woven
Collar Lining	Black Polyester Mesh
Heel Grip	Black Polyester Mesh

<b>Standard Compliance</b>	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 22.08 mm (> 14mm Std)
Toe Compression 1500 N	Clearance 23.26 mm (>14mm Std)

### Miscellaneous

Collar Padding	24 mm Foam Density 30
Zipper	Zipper 120 mm Black
Inner counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

### Outsole

Material	Nitrile
Hardness	65 - 70 Shore A
Antistatic	16.6 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	300°C



**Steel toe protects from impact and compression**



**Strong and durable nitrile rubber outsole**



**Heat resistant up to 300 C**



**Acid and alkali resistant soles**



**PU Insole improves heel cushioning**



# NITRILE

## 2180 H

- Nitrile Rubber
- Heat Resistant (Up to 300 C)
- Steel Safety Toe
- Chemical Resistant Outsole



Brand	Cheetah
Product Line	Nitrile
Description	Lace Up Ankle Boot
Sizes	4 – 12 ( UK )
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Sole	Nitrile
Insock	AIRGO PU™ Comfort Insole
Weight (Approx. Size 7)	700 grams

### Upper Material

Vamp	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter In	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter Out	Full Grain Buffalo Leather 1.8-2.0 Black
Back counter	Full Grain Buffalo Leather 1.8-2.0 Black
Collar	Pvc R 38 Black Backing TPE 0.8 mm
Tongue	Pvc R 38 Black Backing TPE 0.8 mm
Tongue Label	"Animal CHEETAH" Polyester Label
Quarter Label	Label Cheetah Tab TPR Red

### Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Mesh Black
Collar Lining	Mesh Black

<b>Standard Compliance</b>	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 22.08mm (> 14mm Std)
Toe Compression 1500 N	Clearance 23.26mm (>14mm Std)

### Miscellaneous

Collar Padding	24 mm Foam Density 30
Tongue padding	8 mm Foam Density 30
Lace	Round Ø 4.0 mm Black 90 Cm
Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

### Outsole

Material	Nitrile
Hardness	65 - 70 Shore A
Antistatic	16.6 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	300°C

-  Steel toe protects from impact and compression
-  Strong and durable nitrile rubber outsole
-  Heat resistant up to 300 C
-  Acid and alkali resistant soles
-  PU Insole improves heel cushioning





# REVOLUTION

## 3001 H

- Single PU Outsole
- Steel Midsole (Optional)
- Steel Safety Toe
- Economical Pricing



Brand	CHEETAH
Product Line	Revolution
Description	Low Cut Lace Up Shoes
Sizes	4 – 12 ( UK )
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Insock	Eva Foam, 7 mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	514 grams

### Upper Material

Apron	Split Buffalo Leather 1.8-2.0 Black
Vamp In	Split Buffalo Leather 1.8-2.0 Black
Vamp Out	Split Buffalo Leather 1.8-2.0 Black
Quarter IN	Split Buffalo Leather 1.8-2.0 Black
Quarter Out	Split Buffalo Leather 1.8-2.0 Black
Back counter	Split Buffalo Leather 1.8-2.0 Black
Quarter Label	Cheetah Tab TPR Red

### Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Black Polyester Mesh
Collar Lining	Black Polyester Mesh

<b>Standard Compliance</b>	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm ( > 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm ( >14mm Std )

### Miscellaneous

Collar Padding	24 mm Foam Density 30
Inner counter	Thermoplastic heel counter
Thread	Thread Bonded Nylon

### Outsole

Material	Single Density Polyurethane Black
Hardness	57- 63 Shore A
Antistatic	Yes Dry: 264 MΩ ( 0.1 – 1000 MΩ Std ) Wet: 20.6 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



**Steel toe protects from impact and compression**



**Flexible and light to reduce fatigue**



**Slip resistant outsole**



# REVOLUTION

## 3002 H



- Single PU Outsole
- Steel Midsole (Optional)
- Steel Safety Toe
- Economical Pricing

Brand	CHEETAH
Product Line	Revolution
Description	Low Cut Lace Up Shoes
Sizes	4 – 12 ( UK )
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Insock	Eva Foam, 7 mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	495 grams

### Upper Material

Vamp	Split Buffalo Leather 1.8-2.0 Black
Quarter IN	Split Buffalo Leather 1.8-2.0 Black
Quarter Out	Split Buffalo Leather 1.8-2.0 Black
Back counter	Split Buffalo Leather 1.8-2.0 Black
Collar	Pvc R 38 Black Backing TPE 0.8
Tongue	Pvc R 38 Black Backing TPE 0.8
Tongue Logo	"Animal CHEETAH" Polyester Label
Quarter Label	Cheetah Tab TPR Red

### Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Black Polyester Mesh
Quarter/Collar Lining	Black Polyester Mesh

<b>Standard Compliance</b>	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm ( > 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm ( >14mm Std )

### Miscellaneous

Collar Padding	24 mm Foam Density 30
Tongue Padding	8 mm Foam Density 30
Lace	Lace Ø 4.0 mm Black
Inner counter	Thermoplastic heel counter
Eyelet	Hexagonal
Thread	Thread Bonded Nylon

### Outsole

Material	Single Density Polyurethane Black
Hardness	57- 63 Shore A
Antistatic	Yes Dry: 264 MΩ ( 0.1 – 1000 MΩ Std ) Wet: 20.6 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



**Steel toe protects from impact and compression**



**Flexible and light to reduce fatigue**



**Slip resistant outsole**



# REVOLUTION

## 3180 H

- Single PU Outsole
- Steel Midsole (Optional)
- Steel Safety Toe
- Economical Pricing



Brand	CHEETAH
Product Line	Revolution
Description	Mid Cut Lace Up Shoes
Sizes	4 – 12 ( UK )
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Insock	<i>Eva Foam, 7 mm</i>
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	495 grams

### Upper Material

Vamp	Split Buffalo Leather 1.8-2.0 Black
Quarter IN	Split Buffalo Leather 1.8-2.0 Black
Quarter Out	Split Buffalo Leather 1.8-2.0 Black
Back counter	Split Buffalo Leather 1.8-2.0 Black
Collar	Pvc R 38 Black Backing TPE 0.8
Tongue	Pvc R 38 Black Backing TPE 0.8
Tongue Logo	"Animal CHEETAH" Polyester Label
Quarter Label	Cheetah Tab TPR Red

### Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Black Polyester Mesh
Quarter/Collar Lining	Black Polyester Mesh

<b>Standard Compliance</b>	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm ( > 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm ( >14mm Std )

### Miscellaneous

Collar Padding	24 mm Foam Density 30
Tongue Padding	8 mm Foam Density 30
Lace	Lace Ø 4.0 mm Black
Inner counter	Thermoplastic heel counter
Eyelet	Hexagonal
Thread	Thread Bonded Nylon

### Outsole

Material	Single Density Polyurethane Black
Hardness	57- 63 Shore A
Antistatic	Yes Dry: 264 MΩ ( 0.1 – 1000 MΩ Std ) Wet: 20.6 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



**Steel toe protects from impact and compression**



**Flexible and light to reduce fatigue**



**Slip resistant outsole**



# REVOLUTION

## 3286 H

- Single PU Outsole
- Steel Midsole (Optional)
- Steel Safety Toe
- Economical Pricing



Brand	CHEETAH
Product Line	Revolution
Description	High Cut Lace Up Shoes
Sizes	4 – 12 ( UK )
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Insock	<i>Eva Foam, 7 mm</i>
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	614 grams

### Upper Material

Vamp	Split Buffalo Leather 1.8-2.0 Black
Quarter IN	Split Buffalo Leather 1.8-2.0 Black
Quarter Out	Split Buffalo Leather 1.8-2.0 Black
Back counter	Split Buffalo Leather 1.8-2.0 Black
Eyestay	Split Buffalo Leather 1.8-2.0 Black
Collar	Pvc R 38 Black Backing TPE 0.8
Tongue	Pvc R 38 Black Backing TPE 0.8
Quarter Underlay / Window	Cordura Ripstop Diamond Black
Tongue	Cordura Ripstop Diamond Black
Tongue Logo	"Animal CHEETAH" Polyester Label

### Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Black Polyester Mesh
Quarter/Collar Lining	Black Polyester Mesh

<b>Standard Compliance</b>	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm ( > 14mm Std )
Toe Compression 1500 N	Clearance 20.5 mm ( >14mm Std )

### Miscellaneous

Collar Padding	24 mm Foam Density 30
Tongue Padding	8 mm Foam Density 30
Lace	Lace Ø 4.0 mm Black 140 Cm
Inner counter	Thermoplastic heel counter
Eyelet	D Ring Gun Metal
Thread	Thread Bonded Nylon

### Outsole

Material	Single Density Polyurethane Black
Hardness	57- 63 Shore A
Antistatic	Yes Dry: 264 MΩ ( 0.1 – 1000 MΩ Std ) Wet: 20.6 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



**Steel toe protects from impact and compression**



**Flexible and light to reduce fatigue**



**Slip resistant outsole**



# women

## 4007 H

- Single PU Outsole
- Steel Midsole (Optional)
- Steel Safety Toe
- Made for Women Fit



Brand	CHEETAH
Product Line	Women
Description	Low Cut Lace Up Shoes
Sizes	35 – 40 ( Euro )
Last	AHG
Safety Toecap	Steel
Nail Protection	Optional
Insock	Eva Foam, 7 mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	394 grams

### Upper Material

Apron	Full Grain Buffalo Leather 1.8-2.0 Black
Vamp In	Full Grain Buffalo Leather 1.8-2.0 Black
Vamp Out	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter IN	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter Out	Full Grain Buffalo Leather 1.8-2.0 Black
Back counter	Full Grain Buffalo Leather 1.8-2.0 Black
Toe bumper	PU Coated Leather 1.8-2.0 Black
Heel bumper	PU Coated Leather 1.8-2.0 Black
Tongue	Pvc R 38 Black Backing TPE 0.8
Webbing	Webbing 12 mm Base Magenta
Tongue Label	"Animal CHEETAH" Polyester Label

### Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Mesh Lining Magenta
Collar Lining	Mesh Lining Magenta

<b>Standard Compliance</b>	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm ( > 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm ( >14mm Std )

### Miscellaneous

Collar Padding	24 mm Foam Density 30
Tongue Padding	8 mm Foam Density 30
Inner counter	Thermoplastic heel counter
Lace	Lace Ø 3.0 mm Black / Magenta
Thread	Thread Bonded Nylon

### Outsole

Material	Single Density Polyurethane Black
Hardness	57- 63 Shore A
Antistatic	Yes Dry: 264 MΩ ( 0.1 – 1000 MΩ Std ) Wet: 20.6 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Steel toe protects from impact and compression



Flexible and light to reduce fatigue



Made for women's feet for lasting comfort







# REBOUND



## 7001 H

- Double PU Outsole
- Steel Midsole (Optional)
- Steel Safety Toe
- Durable Grain Upper

Brand	CHEETAH
Product Line	Rebound
Description	Low cut slip on shoes
Sizes	4 – 12 ( UK )
Last	701S
Safety Toecap	Steel
Nail Protection	Optional
Sole	Dual PU Antistatic
Insock	Eva Foam, 7 mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	597 grams

### Upper Material

Vamp	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter IN	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter Out	Full Grain Buffalo Leather 1.8-2.0 Black
Back counter	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter Label	Cheetah Tab TPR Red

### Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Black Polyester Mesh
Collar Lining	Black Polyester Mesh

<b>Standard Compliance</b>	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm ( > 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm ( >14mm Std)

### Miscellaneous

Collar Padding	24 mm Foam Density 30
Tongue padding	8 mm Foam Density 30
Inner counter	Thermoplastic heel counter
Thread	Thread Bonded Nylon

### Outsole

Material	Dual Density Polyurethane Black / Gray
Hardness	Out sole : 62 - 68 Shore A ( Gray ) Mid sole : 45 - 51 Shore A ( Black )
Antistatic	Yes Dry: 312 MΩ ( 0.1 – 1000 MΩ Std ) Wet: 21.7 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Steel toe protects from impact and compression



Enhanced shock absorption for all day comfort



Durable and long-lasting genuine leather upper



Improved slip resistance





# REBOUND



## 7012 H

- Double PU Outsole
- Steel Midsole (Optional)
- Steel Safety Toe
- Durable Grain Upper

Brand	CHEETAH
Product Line	Rebound
Description	Low Cut Lace Up Shoes
Sizes	4 – 12 ( UK )
Last	701S
Safety Toecap	Steel
Nail Protection	Optional
Sole	Dual PU Antistatic
Insock	Eva Foam, 7 mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	565 grams

### Upper Material

Vamp	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter IN	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter Out	Full Grain Buffalo Leather 1.8-2.0 Black
Back counter	Full Grain Buffalo Leather 1.8-2.0 Black
Collar	Pvc R 38 Black Backing TPE 0.8
Tongue Logo	"Animal CHEETAH" Polyester Label
Quarter Label	Cheetah Tab TPR Red
Piping	Reflective

### Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Black Polyester Mesh
Quarter/Collar Lining	Black Polyester Mesh

<b>Standard Compliance</b>	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm ( > 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm ( >14mm Std )

### Miscellaneous

Collar Padding	24 mm Foam Density 30
Tongue Padding	8 mm Foam Density 30
Lace	Lace Ø 4.0 mm Black
Inner counter	Thermoplastic heel counter
Accessoris	D Ring
Thread	Thread Bonded Nylon

### Outsole

Material	Dual Density Polyurethane Black / Gray
Hardness	Out sole : 62 - 68 Shore A ( Gray ) Mid sole : 45 - 51 Shore A ( Black )
Antistatic	Yes Dry: 312 MΩ ( 0.1 – 1000 MΩ Std ) Wet: 21.7 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



**Steel toe protects from impact and compression**



**Enhanced shock absorption for all day comfort**



**Durable and long-lasting genuine leather upper**



**Improved slip resistance**



# REBOUND

## 7106 H

- Double PU Outsole
- Steel Midsole (Optional)
- Steel Safety Toe
- Durable Grain Upper



Brand	CHEETAH
Product Line	Rebound
Description	Mid Cut Lace Up Shoes
Sizes	4 – 12 ( UK )
Last	701S
Safety Toecap	Steel
Nail Protection	Optional
Sole	Dual PU Antistatic
Insock	Eva Foam, 7 mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	667 grams

### Upper Material

Vamp	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter IN	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter Out	Full Grain Buffalo Leather 1.8-2.0 Black
Back counter	Full Grain Buffalo Leather 1.8-2.0 Black
Tongue	Full Grain Buffalo Leather 1.0-1.2 Black
Collar	Pvc R 38 Black Backing TPE 0.8
Tongue Logo	"Animal CHEETAH" Polyester Label
Quarter Label	Cheetah Tab TPR Red

### Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Black Polyester Mesh
Collar Lining	Black Polyester Mesh

<b>Standard Compliance</b>	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm ( > 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm ( >14mm Std )

### Miscellaneous

Collar Padding	24 mm Foam Density 30
Lace	Lace Ø 4.0 mm Black
Inner counter	Thermoplastic heel counter
Accessoris	D Ring
Thread	Thread Bonded Nylon

### Outsole

Material	Dual Density Polyurethane Black / Gray
Hardness	Out sole : 62 - 68 Shore A ( Gray ) Mid sole : 45 - 51 Shore A ( Black )
Antistatic	Yes Dry: 312 MΩ ( 0.1 – 1000 MΩ Std ) Wet: 21.7 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Steel toe protects from impact and compression



Enhanced shock absorption for all day comfort



Durable and long-lasting genuine leather upper



Improved slip resistance













## 6112 C

- Double PU Outsole
- Composite Safety Toe
- SoleGard™
- Water Resistant



Brand	Cheetah
Product Line	ADV
Product Name	Jubatus
Description	Ankle Boots with Quick-Lace™
Sizes	4 – 12 ( UK )
Last	701C
Safety Toecap	Composite
Nail Protection	Solegard™ metal free nail-proof midsole
Insock	AIRGO PU™ Comfort Insole
Weight (Approx. Size 7)	665 grams

### Upper Material

Vamp	Leather Loc Brown S-2 1.8-2.0 mm
Mudguard	Leather Loc Brown S-2 1.8-2.0 mm
Quarter	Leather Loc Brown S-2 1.8-2.0 mm
Lacing Eyestay	Leather Loc Brown S-2 1.8-2.0 mm
Tongue Patch Top / Bottom	Leather Loc Brown S-2 1.8-2.0 mm
Toe bumper	PU Coated Leather Black 1.8-2.0 mm
Heel bumper	PU Coated Leather Black 1.8-2.0 mm
Eyelet/Lacing System	Quick-Lace™ System
Collar	Ripstop Black polyester
Tongue	Ripstop Black polyester
Quarter Window	Ripstop Black polyester
Emboss / Printing	"ADV" Toe Bumper

### Lining

Vamp Lining	Grey polyester
Tongue Lining	DryMax™ gore mesh polyester
Collar Lining	DryMax™ gore mesh polyester

<b>Standard Compliance</b>	EN 20345 S3 SRC, ASTM F-2413-11, SNI 7079
Toe Impact 200 Joules	Clearance 22.2mm (> 14mm Std)
Toe Compression 1500 N	Clearance 22.6mm (>14mm Std)

### Miscellaneous

Collar Padding	24 mm Foam
Tongue padding	8 mm Foam
Webbing	12mm Black/Silver Reflective
Insole	Ibisafe 31 Conductive White 2.8mm
Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

### Outsole

Material	Dual Density Polyurethane Black / Gray With TPU Red Insert
Hardness	Out sole : 62 - 68 Shore A Mid sole : 45 - 51 Shore A
Antistatic	Yes Dry: 312 MΩ ( 0.1 – 1000 MΩ Std ) Wet: 21.7 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C

-  Lightweight composite toe protection
-  Enhanced shock absorption for all day comfort
-  Metal free nail-proof midsole
-  PU Insole improves heel cushioning
-  Water resistant upper keeps feet dry





## 6112 G

- Double PU Outsole
- Composite Safety Toe
- SoleGard™
- Water Resistant



Brand	Cheetah
Product Line	ADV
Product Name	Jubatus Forest
Description	Ankle Boots with Quick-Lace™ System
Sizes	4 – 12 ( UK )
Last	701C
Safety Toecap	Composite
Nail Protection	Solegard™ Metal free anti penetration midsole
Insock	AIRGO PU™ COMFORT INSOLE
Weight (Approx. Size 7)	665 grams

### Lining

Vamp Lining	Grey polyester
Tongue Lining	DryMax™ goremesh polyester
Collar Lining	DryMax™ goremesh polyester

### Miscellaneous

Collar Padding	24 mm Foam
Tongue padding	8 mm Foam
Back strap	12mm Black/Silver reflective
Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

### Outsole

Material	Dual Density Polyurethane Black / Taupe With TPU Red Insert
Hardness	Out sole : 62 - 68 Shore A ( Taupe ) Mid sole : 45 - 51 Shore A ( Black )
Antistatic	Yes Dry: 312 MΩ ( 0.1 – 1000 MΩ Std ) Wet: 21.7 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C

### Upper Material

Vamp	Nubuck Leather 1.8-2.0 Rifle Green
Mudguard	Nubuck Leather 1.8-2.0 Rifle Green
Quarter	Nubuck Leather 1.8-2.0 Rifle Green
Lacing Eyestay	Nubuck Leather 1.8-2.0 Rifle Green
Tongue Patch Top / Bottom	Nubuck Leather 1.8-2.0 Rifle Green
Toe bumper	Asphalt Leather 1.8-2.0 Black
Heel bumper	Asphalt Leather 1.8-2.0 Black
Eyelet/Lacing System	Quick-Lace™ System
Collar	Cordura Ripstop Black polyester
Tongue	Cordura Ripstop Black polyester
Quarter Window	Cordura Ripstop Black polyester
Emboss / Printing	"ADV" Toe Bumper

### Standard Compliance

Standard Compliance	EN 20345 S3 SRC, ASTM F2413-11, SNI 7079
Toe Impact 200 Joules	Clearance 22.2mm (> 14mm Std)
Toe Compression 1500 N	Clearance 22.64mm (>14mm Std)



Lightweight composite toe protection



Enhanced shock absorption for all day comfort



Metal free nail-proof midsole



PU Insole improves heel cushioning



Water resistant upper keeps feet dry



## 6012 C

- Double PU Outsole
- Composite Safety Toe
- SoleGard™
- Water Resistant



Brand	CHEETAH
Product Line	ADV
Product Name	NYX
Description	Ankle Boots with Quick-Lace™ System
Sizes	4 – 12 ( UK )
Last	701C
Safety Toecap	Composite
Nail Protection	Solegard™ Metal free nail proof midsole
Insock	AIRGO PU™ Comfort Insole
Weight (Approx. Size 7)	651 grams

### Upper Material

Vamp	Leather Loc Brown S-2 1.8-2.0 mm
Mudguard	Leather Loc Brown S-2 1.8-2.0 mm
Quarter	Leather Loc Brown S-2 1.8-2.0 mm
Lacing Eyestay	Leather Loc Brown S-2 1.8-2.0 mm
Tongue Patch Top	Leather Loc Brown S-2 1.8-2.0 mm
Toe bumper	PU Coated Leather Black 1.8-2.0mm
Heel bumper	PU Coated Leather Black 1.8-2.0mm
Eyelet/Lacing System	Quick-Lace™ System
Collar	Ripstop Black polyester
Tongue	Ripstop Black polyester
Quarter Window	Ripstop Black polyester
Emboss / Printing	"ADV" Toe Bumper

### Lining

Vamp Lining	Grey polyester
Tongue Lining	DryMax™ goremesh polyester
Collar Lining	DryMax™ goremesh polyester

<b>Standard Compliance</b>	EN 20345 S3 SRC, ASTM F2413-11, SNI 7079
Toe Impact 200 Joules	Clearance 22.2mm (> 14mm Std)
Toe Compression 1500 N	Clearance 22.64mm (>14mm Std)

### Miscellaneous

Collar Padding	24 mm Foam
Tongue padding	8 mm Foam
Piping	12mm Black/Silver reflective
Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

### Outsole

Material	Dual Density Polyurethane Black / Gray With TPU Red Insert
Hardness	Out sole : 62 - 68 Shore A Mid sole : 45 - 51 Shore A
Antistatic	Yes Dry: 312 MΩ ( 0.1 – 1000 MΩ Std ) Wet: 21.7 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C

-  Lightweight composite toe protection
-  Enhanced shock absorption for all day comfort
-  Metal free nail-proof midsole
-  PU insole improves heel cushioning
-  Water resistant upper keeps feet dry





## 6110 C

- Double PU Outsole
- Composite Safety Toe
- SoleGard™
- Water Resistant



Brand	CHEETAH
Product Line	ADV
Product Name	Pardus
Description	Ankle boots with elastic side
Sizes	4 – 12 ( UK )
Last	701C
Safety Toecap	Composite
Nail Protection	Solegard™ Metal free anti penetration midsole
Insock	AIRGO PU™ COMFORT INSOLE
Weight (Approx. Size 7)	684 grams

### Upper Material

Vamp	Buffalo Leather Waxy Brown S2 1.8-2.0mm
Front Quarter	Buffalo Leather Waxy Brown S2 1.8-2.0mm
Rear Quarter	Buffalo Leather Waxy Brown S2 1.8-2.0mm
Toe Cap	PU Coated Leather Black 1.8-2 mm
Back strap	PU Coated Leather Black 1.8-2 mm
Webbing	Webbing Cheetah Black
Elastic	Elastic Gore Brown CHEETAH
Piping	Reflective Piping Silver
Emboss / Printing	"ADV" Toe Bumper

### Lining

Vamp Lining	Grey non woven
Quarter Lining	DryMax™ goremesh polyester

### Miscellaneous

Insole	Ibisafe 31 Conductive White 2.8mm
Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

<b>Standard Compliance</b>	EN 20345 S3 SRC, ASTM F2413-11, SNI 7079
Toe Impact 200 Joules	Clearance 22.2mm (> 14mm Std)
Toe Compression 1500 N	Clearance 22.64mm (>14mm Std)

### Outsole

Material	Dual Density Polyurethane Black / Gray With TPU Red Insert
Hardness	Out sole : 62 - 68 Shore A Mid sole : 45 - 51 Shore A
Antistatic	Yes Dry: 312 MΩ ( 0.1 – 1000 MΩ Std ) Wet: 21.7 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Lightweight composite toe protection



Enhanced shock absorption for all day comfort



Metal free nail-proof midsole



PU Insole improves heel cushioning



Water resistant upper keeps feet dry



# CHEETAH Reflex™

## 8083

- Double PU Outsole
- Composite Safety Toe
- SoleGard™
- Water Resistant



Brand	Cheetah
Product Line	Reflex
Product Name	Reflex 8083
Description	Lace up Sport Safety Shoes
Sizes	5 – 12 ( UK )
Last	701 F
Safety Toecap	Composite Fiberglass
Nail Protection	Solegard™ metal free nail-proof midsole
Insock	Insock Foam Red Black 150
Weight (Approx. Size 7)	498 grams

### Upper Material

Vamp	Textile Knit Upper Cheetah Grey
Eyestay	Danaces Black Translucent
Eyestay Backer	Danaces Black Translucent
Toe bumper	PU Coated Leather Black 1.8-2.0 mm
Heel bumper	PU Coated Leather Black 1.8-2.0 mm
Lace	Lace 5mm Lime
Webbing	20 mm CHEETAH Black / Lime
Reinforce	Nonwoven Black
Emboss / Printing	" R " Toe Bumper

### Lining

Vamp Lining	Grey polyester
Tongue Lining	Black Polyester Mesh
Collar Lining	Black Polyester Mesh

<b>Standard Compliance</b>	EN 20345 S1 P SRC, ASTM F-2413-11, SNI 7079
Toe Impact 200 Joules	Clearance 22.2mm (> 14mm Std)
Toe Compression 1500 N	Clearance 22.6mm (>14mm Std)

### Miscellaneous

Collar Padding	8 mm Foam
Insole	Ibisafe 31 Conductive White 3.6mm
Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

### Outsole

Material	Dual Density Polyurethane Black / Lime
Hardness	Out sole : 62 - 68 Shore A Mid sole : 45 - 51 Shore A
Antistatic	Yes Dry: 312 MΩ ( 0.1 – 1000 MΩ Std ) Wet: 21.7 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Lightweight composite toe protection



Enhanced shock absorption for all day comfort



Nail Proof SoleGard™ Midsole



PU Insole improves heel cushioning



Breathable AirKnit™ Upper

# CHEETAH Reflex™

## 8084

- Double PU Outsole
- Composite Safety Toe
- SoleGard™
- Water Resistant



Brand	Cheetah
Product Line	Reflex
Product Name	Reflex 8084
Description	Lace up Sport Safety Shoes
Sizes	5 – 12 ( UK )
Last	701 F
Safety Toecap	Composite Fiberglass
Nail Protection	Solegard™ metal free nail-proof midsole
Insock	Insock Foam Red Black 150
Weight (Approx. Size 7)	498 grams

### Upper Material

Vamp	Textile Knit Upper Cheetah Black
Eyestay	Danaces Black Translucent
Eyestay Backer	Danaces Black Translucent
Toe bumper	PU Coated Leather Black 1.8-2.0 mm
Heel bumper	PU Coated Leather Black 1.8-2.0 mm
Lace	Lace 5mm Red
Webbing	20 mm CHEETAH Black / Red
Reinforce	Nonwoven Black
Emboss / Printing	" R " Toe Bumper

### Lining

Vamp Lining	Grey polyester
Tongue Lining	Black Polyester Mesh
Collar Lining	Black Polyester Mesh

<b>Standard Compliance</b>	EN 20345 S1 P SRC, ASTM F-2413-11, SNI 7079
Toe Impact 200 Joules	Clearance 22.2mm (> 14mm Std)
Toe Compression 1500 N	Clearance 22.6mm (>14mm Std)

### Miscellaneous

Collar Padding	8 mm Foam
Insole	Ibisafe 31 Conductive White 3.6mm
Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

### Outsole

Material	Dual Density Polyurethane Black / Red
Hardness	Out sole : 62 - 68 Shore A Mid sole : 45 - 51 Shore A
Antistatic	Yes Dry: 312 MΩ ( 0.1 – 1000 MΩ Std ) Wet: 21.7 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Lightweight composite toe protection



Enhanced shock absorption for all day comfort



Nail Proof SoleGard™ Midsole



PU Insole improves heel cushioning



Breathable AirKnit™ Upper



## 6288 C

- Double PU Outsole
- Composite Safety Toe
- SoleGard™
- Water Resistant



### Upper Material

Brand	Cheetah
Product Line	ADV
Product Name	Rigger
Description	Pull up "Rigger" Boots
Sizes	4 – 12 ( UK )
Last	701C
Safety Toecap	Composite
Nail Protection	Solegard™ Metal free anti penetration midsole
Insock	AIRGO PU™ Comfort Insole
Weight (Approx. Size 7)	806 grams

Vamp	Leather Loc Brown S-2 1.8-2.0 mm
Front Quarter	Leather Loc Brown S-2 1.8-2.0 mm
Rear Quarter	Leather Loc Brown S-2 1.8-2.0 mm
Back Strap	Leather Loc Brown S-2 1.8-2.0 mm
Quarter Loop	Leather Loc Brown S-2 1.8-2.0 mm
Toe Cap	Leather Coated Black 1.8-2.0 mm
Back Counter	Leather Coated Black 1.8-2.0mm
Collar	Ripstop Black Polyester
Side Logo	Emboss CHEETAH
Emboss / Printing	"ADV" Toe Bumper

### Lining

Vamp Lining	Grey polyester
Collar Lining	DryMax™ gore mesh polyester

### Miscellaneous

Collar Foam	8 mm Foam Density 30
Piping	Reflective Piping Silver
Reflective	Reflective Tape Silver
Inner Counter	Thermoplastic sheet
Insole	Ibsafe 31 Conductive White 2.8mm
Thread	Thread Bonded Nylon

<b>Standard Compliance</b>	EN 20345 S3 SRC, ASTM F-2413-11, SNI 7079
Toe Impact 200 Joules	Clearance 22.2 mm (> 14mm Std)
Toe Compression 1500 N	Clearance 22.6 mm (>14mm Std)

### Outsole

Material	Dual Density Polyurethane Black / Gray With TPU Red Insert
Hardness	Out sole : 62 - 68 Shore A Mid sole : 45 - 51 Shore A
Antistatic	Yes Dry: 312 MΩ ( 0.1 – 1000 MΩ Std ) Wet: 21.7 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Lightweight composite toe protection



Enhanced shock absorption for all day comfort



Metal free nail-proof midsole



PU Insole improves heel cushioning



Water resistant upper keeps feet dry



## PRODUCT SPECIFICATION

### Model: 2288H



Model	2288H
Brand	CHEETAH
Product Line	Nitrile
Product Name	Trailblazer
Description	Pull Up " Rigger " Boots
Sizes	4 - 12
Last	130- 2G3
Safety Toecap	130
Nail Protection	Optional
Sole	Nitrile
Insock	CHEETAH™ Airgonomic Footbed Soft EVA, 7mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	800 grams
Upper Material	
Vamp	Genuine Grain Leather Celtic Print 1.8-2.0 Black
Front Quarter	Genuine Grain Leather Celtic Print 1.8-2.0 Black
Rear Quarter	Genuine Grain Leather Celtic Print 1.8-2.0 Black
Back Counter	Genuine Grain Leather Celtic Print 1.8-2.0 Black
Quarter Loop	Genuine Grain Leather Celtic Print 1.8-2.0 Black
Binding	PVC R 38 Black Backing TPE Tebal 0.8 mm
Lining	
Vamp Lining	Grey polyester
Miscellaneous	
Inner Counter	Thermoplastic sheet
Outsole	
Material	Nitrile
Hardness	70 Shore A
Antistatic	16.6 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Suitable

# PRODUCT SPECIFICATION

## Model: 2288H

Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	300°C
Standard Compliance	EN 20345 S1 SRC, SNI 7079
Toe Impact 200 Joules	Clearance 22.08 mm (> 14mm Std)
Toe Compression 1500 N	Clearance 23.26 mm (>14mm Std)

Jakarta, April 20<sup>th</sup> 2020



**CHEETAH**  
PT. FORTA-LARESE  
BOGOR

Riskan Syahrul  
Quality & Product Tehnical Exeective

## PRODUCT SPECIFICATION

### Model: 2291H



Model	2291H
Brand	CHEETAH
Product Line	Nitrile
Product Name	Trailblazer
Description	Welder boots with adjustable velcro straps
Sizes	4 - 12
Last	130- 2G3
Safety Toecap	130
Nail Protection	Optional
Sole	Nitrile
Insock	CHEETAH™ Airgonomic Footbed Soft EVA, 7mm
ESD/Antistatic	Antistatic
Height of the upper	9 Inch
Weight (Approx. Size 7)	785 grams
Upper Material	
Vamp	Genuine Grain Leather Celtic Print 2.0 – 2.2 mm Black
Quarter IN / Out	Genuine Grain Leather Celtic Print 2.0 – 2.2 mm Black
Back Counter	Genuine Grain Leather Celtic Print 2.0 – 2.2 mm Black
Back Strap	Genuine Grain Leather Celtic Print 2.0 – 2.2 mm Black
Strap	Genuine Grain Leather Celtic Print 2.0 – 2.2 mm Black
Tongue	Genuine Grain Leather Celtic Print 1.0 – 1.2 mm Black
Collar	Genuine Grain Leather Celtic Print 1.0 – 1.2 mm Black
Lining	
Vamp Lining	Grey polyester
Quarter Lining	Non Woven Cambrelle Lining Black
Miscellaneous	
Inner Counter	Thermoplastic sheet
Outsole	
Material	Nitrile
Hardness	70 Shore A

# PRODUCT SPECIFICATION

## Model: 2291H

<b>Antistatic</b>	16.6 MΩ ( 0.1 – 1000 MΩ Std )
<b>Oil Resistance</b>	Suitable
<b>Acid &amp; Alkali</b>	Suitable
<b>Vegetable Oil &amp; Animal Fats</b>	Suitable
<b>Wet &amp; Humid Condition</b>	Good
<b>Severe Surface Abrasion</b>	Good
<b>Heat Resistance (Short Term)</b>	300°C
<b>Standard Compliance</b>	EN 20345 S1 SRC, SNI 7079
<b>Toe Impact 200 Joules</b>	Clearance 22.08 mm (> 14mm Std)
<b>Toe Compression 1500 N</b>	Clearance 23.26 mm (>14mm Std)

Jakarta, June 25<sup>th</sup> 2020



**CHEETAH**<sup>®</sup>  
PT. FORTA-LARESE  
BOGOR

## PRODUCT SPECIFICATION

### Model: 7001H



Model	7001H
Brand	Cheetah
Product Line	Rebound
Product Name	-
Description	Low Cut Slip on Shoes,
Sizes	4 – 12
Last	701 - G3
Safety Toecap	701
Nail Protection	Optional
Sole	Double Density Poly Urethane ( PU )
Insock	CHEETAH™ Airgonomic Footbed Soft EVA, 7mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	486 grams
Upper Material	
Vamp	Genuine Grain Leather Celtic Print 1.8-2.0 Black
Back Counter	Genuine Grain Leather Celtic Print 1.8-2.0 Black
Quarter	Genuine Grain Leather Celtic Print 1.8-2.0 Black
Tongue	Genuine Grain Leather Celtic Print 1.8-2.0 Black
Quarter Label	"CHEETAH" Polyester Label
Lining	
Vamp Lining	Grey polyester
Tongue Lining	Non Woven Cambrelle Lining
Quarter/Collar Lining	Non Woven Cambrelle Lining
Miscellaneous	
Collar Padding	20 mm Foam Density 24
Thread	Thread Bonded Nylon
Inner Counter	Thermoplastic sheet
Outsole	
Material	Double Density Polyurethane Black / Grey
Antistatic	Yes Dry: 317 MΩ ( 0.1 – 1000 MΩ Std ) Wet: 21.2 MΩ ( 0.1 – 1000 MΩ Std )
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable

# PRODUCT SPECIFICATION

## Model: 7001H

Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	200°C
Standard Compliance	EN 20345, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm (> 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm (>14mm Std)

Jakarta, April 20<sup>th</sup> 2020



**CHEETAH**<sup>®</sup>  
PT. FORTA-LARESE  
BOGOR

Riskan Syahrul  
Quality & Product Tehnical Exectutive

## PRODUCT SPECIFICATION

### Model: 7106C



Model	7106C
Brand	Cheetah
Product Line	Rebound
Product Name	-
Description	Lace up Ankle Boot
Sizes	4 – 12
Last	701 - G3
Safety Toecap	701
Nail Protection	Optional
Sole	Double Density Poly Urethane ( PU )
Insock	<i>CHEETAH</i> <sup>TM</sup> Airgonomic Footbed Soft EVA, 7mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	570 grams
Upper Material	
Vamp	Genuine Grain leather Celtic Print 1.8-2.0 mm Brown
Back Counter	Genuine Grain leather Celtic Print 1.8-2.0 mm Brown
Quarter	Genuine Grain leather Celtic Print 1.8-2.0 mm Brown
Tongue	Genuine Grain leather Brown 1.0 – 1.2 mm
Collar	Shyntetic leather 0.8 mm Brown
Lace	Lace Ø 4.0 mm Brown 110 Cm
Quarter Label	“ <i>CHEETAH</i> ” Polyester Label
Tongue Label	“ANIMAL & <i>CHEETAH</i> ” Polyester Label
Lining	
Vamp Lining	Grey polyester
Tongue Lining	Non Woven Cambrelle Lining Black
Quarter/Collar Lining	Non Woven Cambrelle Lining Black
Miscellaneous	
D Ring	D-Ring No Washer Gun metal
Collar Padding	20 mm Foam Density 24
Thread	Thread bonded Nylon
Inner Counter	Thermoplastic sheet
Outsole	

# PRODUCT SPECIFICATION

## Model: 7106C

<b>Material</b>	Double Density Polyurethane Black / Black
<b>Antistatic</b>	Yes Dry: 317 MΩ ( 0.1 – 1000 MΩ Std ) Wet: 21.2 MΩ ( 0.1 – 1000 MΩ Std )
<b>Oil Resistance</b>	Suitable
<b>Acid &amp; Alkali</b>	Not Suitable
<b>Vegetable Oil &amp; Animal Fats</b>	Suitable
<b>Wet &amp; Humid Condition</b>	Good
<b>Severe Surface Abrasion</b>	Good
<b>Heat Resistance (Short Term)</b>	200°C
<b>Standard Compliance</b>	EN 20345 S1 SRC, SNI 7079
<b>Toe Impact 200 Joules</b>	Clearance 16.5 mm (> 14mm Std)
<b>Toe Compression 1500 N</b>	Clearance 20.5 mm (>14mm Std)

Jakarta, April 20<sup>th</sup> 2020



**CHEETAH**  
PT. FORTA-LARESE  
BOGOR

Riskan Syahrul  
Quality & Product Tehnical Executive