



DATA SHEET

HIKVISION[®]

HIKVISION®



KATALOG RETAIL **2024**

www.hikvision.com

Hikvision Lampu Kamera

Smart Hybrid Light



NEW

DS-2CE18D0T-LFS

- 2 MP, 2.8 mm, 3.6 mm and 6 mm fixed focal lens
- Smart Hybrid light
- High quality audio with audio over coaxial cable, built-in mic
- 4 in 1(TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP67)



DS-2CE16D0T-LPFS

DS-2CE16D0T-LFS

- 2MP CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N), EXIR, 25m IR+20m White Light,
- Outdoor Dual-light Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI),
- Smart Lighting With Acusense DVR ,OSD Menu (Up the Coax), IP67,2.8/3.6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal



DS-2CE76D0T-LPFS

DS-2CE76D0T-LMFS

- 2MP CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N), EXIR, 20m IR+20m White Light,
- indoor Dual-light Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI),
- Smart Lighting With Acusense DVR ,OSD Menu (Up the Coax), 2.8/3.6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal



DS-2CE16D0T-EXLPF

DS-2CE16D0T-EXLF

- 2MP CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N), EXIR, 20m IR+20m White Light,
- Outdoor Dual-light Bullet, ICR, 0.02 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67,2.8/3.6mm Lens Support TVI/AHD/CVI/CVBS video signal output
- Smart Lighting With Acusense DVR
- (P) : Plastic, (M) : Metal



DS-2CE76D0T-EXLPF

DS-2CE76D0T-EXLMF

- 2MP CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N), EXIR, 20m IR+20m White Light,
- Outdoor Dual-light Bullet, ICR, 0.02 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67,2.8/3.6mm Lens Support TVI/AHD/CVI/CVBS video signal output
- Smart Lighting With Acusense DVR
- (P) : Plastic, (M) : Metal



DS-2CE17D0T-IT1F

DS-2CE17D0T-IT3F

DS-2CE17D0T-IT5F

- 2MP CMOS Sensor, EXIR 30m IR,
- Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, IP67, 2.8/3.6/6mm Lens,
- Support TVI/AHD/CVI/CVBS video signal output
- (X) : 1 : EXIR 30m IR
3 : EXIR 40m IR
5 : EXIR 80m IR



DS-2CE56D0T-IT1F

DS-2CE56D0T-IT3F

- HD1080p, 2MP CMOS Sensor, 2 pcs EXIR LEDs, 20m IR,
- Outdoor EXIR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens,
- Support TVI/AHD/CVI/CVBS video signal output
- (X) : 1 : EXIR 30m IR
3 : EXIR 40m IR
5 : EXIR 80m IR



DS-2CE16D0T-ITF

- 2MP CMOS Sensor, EXIR, 30m IR,
- Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12VDC,
- Smart IR, OSD Menu(Up the Coax), IP67,2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output



DS-2CE76D0T-ITMF

- 2MP CMOS Sensor, EXIR 30m IR,
- Outdoor EXIR Turret, ICR, 0.01 Lux/F1.2, 12 VDC,
- Smart IR, DNR, OSD Menu(Up the Coax), IP67,2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output

ANALOG 3K



DS-2CE16K0T-LPFS

DS-2CE16K0T-LFS

- 3K 5MP 16:9 CMOS Sensor, 3K @ 20 fps (Default), EXIR, 25m IR+20m White Light,
- Outdoor Dual-light Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI),
- Smart Lighting With Acusense DVR, OSD Menu (Up the Coax), IP67, 2.8/3.6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal



DS-2CE76K0T-LPFS

DS-2CE76K0T-LFS

- 3K 5MP 16:9 CMOS Sensor, 3K @ 20 fps (Default), EXIR, 20m IR+20m White Light,
- indoor Dual-light Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI),
- Smart Lighting With Acusense DVR, OSD Menu(Up the Coax), 2.8/3.6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal



DS-2CE16K0T-EXLPF

DS-2CE16K0T-EXLF

- 3K 5MP 16:9 CMOS Sensor, 3K @ 20 fps (Default), EXIR, 20m IR+20m White Light,
- Outdoor Dual-light Bullet, ICR, 0.02 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.8/3.6mm Lens Support TVI/AHD/CVI/CVBS video signal output
- Smart Lighting With Acusense DVR
- (P) : Plastic, (M) : Metal



DS-2CE76K0T-EXLPF

DS-2CE76K0T-EXLMF

- 3K 5MP 16:9 CMOS Sensor, 3K @ 20 fps (Default), EXIR, 20m IR+20m White Light,
- indoor Dual-light Turret, ICR, 0.02 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), 2.8/3.6mm Lens Support TVI/AHD/CVI/CVBS video signal output
- Smart Lighting With Acusense DVR
- (P) : Plastic, (M) : Metal



DS-2CE19H0T-AIT3ZF

DS-2CE19H8T-AIT3ZF

- 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 80m IR, Auto Focus ,
- Outdoor Bullet, ICR, up to 0.003 Lux/F1.2, 12 VDC/AC24V, Smart IR, True WDR, 3D DNR, OSD Menu (Up the Coax), IP67, 2.7-13.5mm Motorized Vari-focal Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (x) : 0 : Lux 0.01
8 : Lux 0.003



DS-2CE57H0T-VPITF

DS-2CE57H8T-VPITF

- 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 30m IR,
- Outdoor Vandal Proof Dome, ICR, 0.003 Lux/F1.2, 12 VDC, Smart IR, True WDR, 3D DNR, OSD Menu (Up the Coax), IP67, 2.8/3.6/6/8/12mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (x) : 0 : Lux 0.01
8 : Lux 0.003



DS-2CE5AH8T-AVPIT3ZF

DS-2CE59H8T-AVPIT3ZF

DS-2CE56H8T-AITZF

- 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 60m IR, Auto Focus ,
- Outdoor Vandal Proof Dome, ICR, up to 0.003 Lux/F1.2, 12 VDC/AC24V, Smart IR, True WDR, 3D DNR, OSD Menu(Up the Coax), IP67, 2.7-13.5mm Motorized Vari-focal Lens
- Support TVI/AHD/CVI/CVBS video signal output
- V : Outdoor Vandal Proof Dome



DS-2CE16H8T-ITF

DS-2CE16H8T-IT(x)F

DS-2CE16H0T-ITPF(s)

- 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 30m IR,
- Outdoor EXIR Bullet, ICR, 0.003 Lux/F1.2, 12VDC, Smart IR, True WDR, 3D DNR, OSD Menu (Up the Coax), IP67, 2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (X) : 1 : 30m IR
3 : 40m IR
5 : 80m IR



DS-2CE76H0T-ITPF(s)

DS-2CE76H0T-ITMF

DS-2CE76H8T-ITMF

- 5MP@20fps, 4MP@25fps(P)/30fps(N), EXIR, up to 30m IR,
- Outdoor EXIR Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), 2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal
- (S) : Built-in Mic, Audio up Coaxial(Only TVI),
- HOT : 0.01 Lux
H8T : 0.003 Lux

ColorVu

Technology

2MP



NEW

DS-2CE10DF0T-LPFS

DS-2CE10DF0T-LFS

- 2M CMOS Sensor, 2.8/3.6mm Lens
- Outdoor smart hybrid light Bullet 0.001Lux/F1.0 20m IR+20m White Light
- 3D DNR 12 VDC
- Built-in Mic Audio up Coaxial(Only TVI)
- OSD Menu(Up the Coax)
- IP67
- 24H ColorSmart Lighting With Acusense DVR Support TVI/AHD/CVI/CVBS video signal output



NEW

DS-2CE12DF0T-LFS

- 2M CMOS Sensor, 2.8/3.6/6mm Lens 24H Color
- Outdoor smart hybrid light Bullet 0.001Lux/F1.0 40m IR+40m White Light
- 3D DNR
- 12 VDC
- Built-in Mic Audio up Coaxial(Only TVI)
- OSD Menu(Up the Coax)
- IP67
- Smart Lighting With Acusense DVR Support TVI/AHD/CVI/CVBS video signal output



NEW

DS-2CE70DF0T-LPFS

DS-2CE70DF0T-LMFS

- 2M CMOS Sensor, 2.8/3.6mm Lens
- Outdoor smart hybrid light Turret 0.001Lux/F1.0 20m IR+20m White Light
- 3D DNR
- 12 VDC
- Built-in Mic Audio up Coaxial(Only TVI)
- OSD Menu(Up the Coax)
- IP67
- 24H Color Smart Lighting With Acusense DV Support TVI/AHD/CVI/CVBS video signal output



DS-2CE72DF0T-LFS

- 2M CMOS Sensor, 2.8/3.6mm Lens
- Outdoor smart hybrid light Turret 0.001Lux/F1.0 40m IR+40m White Light
- 3D DNR
- 12 VDC
- Built-in Mic Audio up Coaxial(Only TVI) OSD Menu(Up the Coax)
- IP67
- 24H Color Smart Lighting With Acusense DVR Support TVI/AHD/CVI/CVBS video signal output



NEW

DS-2CE10KF0T-L(P)FS

- 3K(5MP 16:9), 2.8 mm, 3.6 mm fixed focal lens
- Smart Hybrid light with ColorVu
- High quality audio with audio over coaxial cable, built-in mic
- Super Confocal F1.0 Lens
- 4 in 1(TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP67)



NEW

DS-2CE12KF0T-LFS

- 3K(5MP 16:9), 2.8 mm, 3.6 mm fixed focal lens
- Smart Hybrid light with ColorVu
- High quality audio with audio over coaxial cable, built-in mic
- Super Confocal F1.0 Lens
- 4 in 1(TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP67)



24/7

Gambar Berwarna

5MP



NEW

DS-2CE70KF0T-LM(P)FS

- 3K(5MP 16:9), 2.8 mm, 3.6 mm fixed focal lens
- Smart Hybrid light with ColorVu
- High quality audio with audio over coaxial cable, built-in mic
- Super Confocal F1.0 Lens
- 4 in 1(TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP67)



NEW

DS-2CE72KF0T-LFS

- 3K(5MP 16:9), 2.8 mm, 3.6 mm fixed focal lens
- Smart Hybrid light with ColorVu
- High quality audio with audio over coaxial cable, built-in mic
- Super Confocal F1.0 Lens
- 4 in 1(TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP67)



DS-2CE10DF3T-(P)F(S)

- 2M BSI CMOS Sensor,
- Outdoor mini Bullet,0.0005Lux/F1.0, 0 Lux with Friendly Lighting,20M,3D DNR,DC 12V, OSD Menu (Up the Coax), 130dB True WDR, IP67, 2.8/3.6mm Lens,
- 24H Color,Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal
- (S) : Built-in Mic,Audio up Coaxial(Only TVI)



DS-2CE12DF3T-F(S)

- 2M BSI CMOS Sensor,
- Outdoor Bullet,0.0005Lux/F1.0, 0 Lux with Friendly Lighting,40M,3D DNR,DC 12V, OSD Menu(Up the Coax), 130dB True WDR, IP67, 2.8/3.6/6mm Lens,
- 24H Color,Support TVI/AHD/CVI/CVBS video signal output
- (S) : Built-in Mic,Audio up Coaxial(Only TVI),



DS-2CE72DF3T-FS

- 2M BSI CMOS Sensor,
- Outdoor Turret,0.0005Lux/F1.0, 0 Lux with Friendly Lighting,40M,3D DNR,DC 12V, OSD Menu(Up the Coax), 130dB True WDR, IP67, 2.8/3.6mm Lens,
- 24H Color,Support TVI/AHD/CVI/CVBS video signal output
- (S) : Built-in Mic,Audio up Coaxial(Only TVI),



DS-2CE70DF3T-(P)F(S)

- 2M BSI CMOS Sensor,
- Indoor Turret,0.0005Lux/F1.0, 0 Lux with Friendly Lighting,20M,3D DNR,DC 12V, OSD Menu(Up the Coax), 130dB True WDR, 2.8/3.6mm Lens,
- 24H Color,Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal
- (S) : Built-in Mic,Audio up Coaxial(Only TVI),

4K IN FULL COLOUR 24/7 WITH LIGHT & SOUND DETERRENCE

Pro Series 8 MP
with Live Guard & ColorVu Technology



DS-2CE16U1T-IT(x)F

DS-2CE16U7T-IT(3)F

- 8.3MP @12.5fps(Default),5MP@20fps, 4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N),
- Outdoor EXIR Bullet , ICR, 0.01 Lux/F1.2, 12VDC, Smart IR,DNR, OSD Menu(Up the Coax), IP67,2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic
- U1T : 0.01 Lux, U7T : 0.003 Lux
- (X) : 1 : 30m IR, 3 : 60m IR, 5 : 80m IR



DS-2CE19U1T-IT3ZF

DS-2CE19U1T-AIT3ZF

- 8.3MP @12.5fps(Default),5MP@20fps, 4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N),EXIR, 80m IR, Auto Focus ,
- Outdoor Bullet,ICR, 0.01 Lux/F1.2, Smart IR, DNR,OSD Menu(Up the Coax), IP67, 2.7-13.5mm Motorized Vari-focal Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (A) : 12VDC/AC24V



DS-2CE56U1T-ITZF

DS-2CE56U1T-AITZF

- 8.3MP @12.5fps(Default),5MP@20fps, 4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N),EXIR, 60m IR, Auto Focus ,
- Indoor Dome,ICR, 0.01 Lux/F1.2,12 VDC/AC24V, Smart IR,DNR,OSD Menu(Up the Coax),2.7-13.5mm Motorized Vari-focal Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (A) : 12VDC/AC24V



DS-2CE57U1T-VPITF

DS-2CE57U7T-VPITF

- 8.3MP @12.5fps(Default),5MP@20fps, 4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N), EXIR, 30m IR,
- Outdoor Vandal Proof Dome, ICR, up to 0.003 Lux/F1.2, 12VDC, Smart IR,DNR, OSD Menu (Up the Coax), IP67,3.6/6/8/12mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- U1T : 0.01 Lux
- U7T : 0.003 Lux



DS-2CE59U1T-(A)VPIT3ZFPIT3ZF

DS-2CE59U7T-AVPIT3ZF

- 8.3MP @12.5fps(Default),5MP@20fps, 4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N), EXIR, 30m IR,
- Indoor EXIR Turret,ICR, up to 0.003 Lux/F1.2, 12VDC, Smart IR,DNR, OSD Menu(Up the Coax), IP67,2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal
- U1T : 0.01 Lux
- U7T : 0.003 Lux



DS-2CE5AU1T-AVPIT3ZF

- 8.3MP @12.5fps(Default),5MP@20fps, 4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N),EXIR, 60m IR, Auto Focus ,
- Outdoor Vandal Proof Dome,ICR, 0.01 Lux/F1.2, 12 VDC/AC24V, Smart IR,DNR,OSD Menu(Up the Coax), IP67, 2.7-13.5mm Motorized Vari-focal Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (A) ; 12VDC/AC24V



DS-2CE76U1T-IT(P)F

DS-2CE76U7T-ITMF

- 8.3MP @12.5fps(Default),5MP@20fps, 4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N), EXIR, 30m IR,
- Indoor EXIR Turret,ICR, up to 0.003 Lux/F1.2, 12VDC, Smart IR,DNR, OSD Menu(Up the Coax), IP67,2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal
- U1T : 0.01 Lux, U7T : 0.003 Lux



DS-2CE78U1T-IT(X)F

DS-2CE78U7T-IT3F

- 8.3MP @12.5fps(Default),5MP@20fps, 4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N), EXIR, 30m IR,
- Outdoor EXIR Turret,ICR, 0.01 Lux/F1.2, 12VDC, Smart IR,DNR, OSD Menu(Up the Coax), IP67,2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- U1T : 0.01 Lux, U7T : 0.003 Lux
- (X) : 1 : 30m IR, 3 : 60m IR



DS-2CE79U1T-IT3ZF

- 8.3MP @12.5fps(Default),5MP@20fps, 4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N),EXIR, 60m IR, Auto Focus ,
- Outdoor Turret,ICR, 0.01 Lux/F1.2,12 VDC, Smart IR,DNR,OSD Menu(Up the Coax), IP67, 2.7-13.5mm Motorized Vari-focal Lens
- Support TVI/AHD/CVI/CVBS video signal output

TURBO HD PTZ



DS-2AE4225TI-D

- 1/2.8" CMOS, 1920x1080:30fps, TVI & CVBS output, 3D DNR, True WDR,
- Ultra-low light Powerde By DarkFighter Color: 0.005lux/F1.6, B/W:0.001lux/F1.6, Optical Zoom:25x, Digital Zoom:16X,
- Pan Speed: 0.1° ~ 80°/s, Tilt Speed: 0.1° ~ 80°/s,
- Up the Coax,100mIR,DC12V



DS-2AE4215TI-D

- 1/2.8" CMOS, 1920x1080:30fps, TVI & CVBS output, 3D DNR,
- Ultra-low light Powerde By DarkFighter Color: 0.005lux/F1.6, B/W:0.001lux/F1.6, Optical Zoom:15x,
- Pan Speed: 0.1° ~ 80°/s, Tilt Speed: 0.1° ~ 80°/s,
- Up the Coax,100m IR,DC12V



DS-2AE4225T-D

DS-2AE4225T-D3

- 1/2.8" CMOS, 1920x1080:30fps, TVI & CVBS output, 3D DNR, True WDR,
- Ultra-low light Powerde By DarkFighter Color: 0.005lux/F1.6, B/W:0.001lux/F1.6,
- Optical Zoom:25x, Digital Zoom:16X,
- Up the Coax,DC12V



DS-2AE4215T-D3

- 1/3" CMOS, 1920x1280:30fps, 3D DNR, ICR, Color: 0.05lux/F1.4, B/W:0.005lux/F1.4, Optical Zoom:15x, Focus:4.0-60mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -5°~90°(Auto Flip),
- Pan Speed: 0.1° ~160°/s, Tilt Speed: 0.1° ~120°/s,
- Up the Coax, 24VAC

COMING
SOON

HIKVISION

Turbo HD 8.0

Wider vision, interactive connection

- POINT 01 – TVI Two-way Audio**
Interactive communication with crystal-clear audio effect
- POINT 02 – Compact Dual-lens Stitching**
Perfect 180-degree stitched images to ensure seamless visuals
- POINT 03 – Upgraded Intelligence**
Improved night vision experience via Smart Hybrid Light; smarter video searching via AcuSearch

Two-way Audio

Smart Hybrid Light

Dual-lens Stitching

AcuSearch



www.hikvision.com
support@hikvision.com



NEW

DarkFighter

FOCUS
and
ACT

AcuSense Technology



NEW

DS-2CD2086G2H-I

DS-2CD2086G2H-IU

DS-2CD2046G2H-I

DS-2CD2046G2H-IU

- 1/1.8" Progressive Scan CMOS;
- 4K:25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
- 4MP:25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ;
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light;
- VCA functions; 3 streams;
- 3D DNR; BLC; ICR; EXIR, Up to 40 m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- U:Built-in microphone



NEW

DS-2CD2186G2H-I

DS-2CD2186G2H-ISU

DS-2CD2146G2H-I

DS-2CD2146G2H-ISU

- 1/1.8" Progressive Scan CMOS;
- 4K:25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
- 4MP:25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ;
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light;
- VCA functions; 3 streams;
- 3D DNR; BLC; ICR; EXIR, Up to 40 m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- U:Built-in microphone



NEW

DS-2CD2386G2H-I

DS-2CD2386G2H-IU

DS-2CD2346G2H-I

DS-2CD2346G2H-IU

- 1/1.8" Progressive Scan CMOS;
- 4K:25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
- 4MP:25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ;
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light;
- VCA functions; 3 streams;
- 3D DNR; BLC; ICR; EXIR, Up to 40 m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- U:Built-in microphone



NEW

DS-2CD2T86G2H-2I

DS-2CD2T86G2H-4I

DS-2CD2T46G2H-2I

DS-2CD2T46G2H-4I

- 1/1.8" Progressive Scan CMOS;
- 25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
- 4MP:25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ;
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light;
- VCA functions; 3 streams;
- 3D DNR; BLC; ICR; EXIR; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- *-2I/4I model: up to 60m(2Leds)/80m(4Leds) IR distance



NEW

DS-2CD2686G2HT-IZS

DS-2CD2646G2HT-IZS

- 1/1.8" Progressive Scan CMOS;
- 25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
- 4MP:25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ;
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.2, AGC ON),0 Lux with light
- VCA functions; 3 streams;
- 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- *Junction box is included in the camera package



NEW

DS-2CD2786G2HT-IZS

DS-2CD2746G2HT-IZS

- 1/1.8" Progressive Scan CMOS;
- 25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
- 4MP:25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ;
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.2, AGC ON),0 Lux with light
- VCA functions; 3 streams;
- 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- *Junction box is included in the camera package

Live Guard

Perlindungan proaktif, sepanjang hari



NEW

DS-2CD2087G2H-LIU/SL

DS-2CD2047G2H-LIU/SL

- 1/1.8" Progressive Scan CMOS;
- 4K:25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080,1280×720);4MP:25ps/30fps (2688× 1520, 1920 × 1080, 1280 × 720);
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light
- VCA functions; 3 streams; 3D DNR; BLC; ICR;
- 3000K Warm LED;IR, up to 40m DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- Built-in microphone and speaker



NEW

DS-2CD2387G2H-LISU/SL

DS-2CD2347G2H-LISU/SL

- 1/1.8" Progressive Scan CMOS;
- 4K:25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080,1280×720);4MP:25ps/30fps (2688× 1520, 1920 × 1080, 1280 × 720);
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light
- VCA functions; 3 streams; 3D DNR; BLC; ICR;
- 3000K Warm LED;IR, up to 40m DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- Built-in microphone and speaker



NEW

DS-2CD2T87G2H-LISU/SL

DS-2CD2T47G2H-LISU/SL

- 1/1.8" Progressive Scan CMOS;
- 4K:25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080,1280×720);4MP:25ps/30fps (2688× 1520, 1920 × 1080, 1280 × 720);
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light
- VCA functions; 3 streams; 3D DNR; BLC; ICR;
- 3000K Warm LED;IR, up to 40m DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- Built-in microphone and speaker



DS-2CD2086G2-IU/SL

DS-2CD2046G2-IU/SL

DS-2CD2026G2-IU/SL

- 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Powered by Darkfighter technology, Color: 0.003 Lux @ (F1.4, AGC ON), 0 lux with IR;
- 4K : 25fps/24fps(3840×2160), 4MP : 25fps/30fps (3200×1800, 2688×1520), 2MP : 25fps/30fps (1920×1080);
- Human / vehicle classification alarm, VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- Built-in microphone and speaker



DS-2CD2047G2-LU/SL (ColorVu)

- Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0005 lux @(F1.0, AGC ON), 0 lux with LED on;
- 4MP : 25fps/30fps (2688×1520); 2MP : 25fps/30fps (1920×1080);
- VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- (U) : Built-in micphone
- (SL) : Built-in microphone and speaker



DS-2CD2386G2-ISU/SL

DS-2CD2346G2-ISU/SL

DS-2CD2326G2-ISU/SL

- 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Powered by Darkfighter technology, Color: 0.003 lux@(F1.4, AGC ON), 0 lux with IR;
- 4K : 20fps(3840×2160), 4MP : 25fps/30fps (3200×1800, 2688×1520), 2MP : 25fps/30fps (1920×1080);
- Human / vehicle classification alarm, VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- Built-in microphone and speaker, Audio/Alarm I/O



DS-2CD2T86G2-ISU/SL

DS-2CD2T46G2-ISU/SL

DS-2CD2T26G2-ISU/SL

- 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Powered by Darkfighter technology, Color: 0.003 lux@(F1.4, AGC ON), 0 lux with IR;
- 4K : 20fps(3840×2160), 4MP : 25fps/30fps (3200×1800, 2688×1520), 2MP : 25fps/30fps (1920×1080);
- Human / vehicle classification alarm, VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- Built-in microphone and speaker, Audio/Alarm I/O

PoE Switch

Cerdas • Kokoh • Aman



DS-3E0105P-E/M

DS-3E0106P-E/M

DS-3E0109P-E/M

- L2, Unmanaged, Up to 8 x 10/100M RJ45 PoE ports, 1 x 10/100M RJ45 uplink port,
- 802.3af/at, PoE power budget 60W, max. 250m long distance transmission, 6KV surgy protection



DS-3E0310P-E/M

DS-3E0318P-E/M

DS-3E0326P-E/M

- L2, Unmanaged, Up to 24 x 10/100M RJ45 PoE ports, 1 Gigabit RJ45 uplink port, 1 Gigabit SFP uplink port,
- 802.3af/at, PoE power budget up to 230W, "Extend" Mode port up to 250meter, 6KV surgy protection



DS-3E0505P-E/M

DS-3E0510P-E/M

DS-3E0518P-E/M

DS-3E0526P-E/M

- L2, Unmanaged, Up to 24 Gigabit POE ports, 2 Gigabit SFP uplink ports,
- 802.3af/at, PoE power budget up to 225w



DS-3E0105P-E

DS-3E0109P-E

DS-3E0318P-E

DS-3E0326P-E

- L2, Unmanaged, Up to 24 x 10/100M RJ45 PoE ports, 2 Gigabit combo ports,
- 802.3af/at, PoE power budget up to 370W, "Extend" Mode ports support up to 250 meter, 6KV surgy protection



DS-3E0505P-E

DS-3E0510P-E

DS-3E0518P-E

DS-3E0526P-E

- L2, Unmanaged, Up to 24 Gigabit POE ports, 1 Gigabit RJ45 uplink port, 1 Gigabit SFP uplink port,
- 802.3af/at, PoE power budget Up to 370w



DS-3E0505HP-E

DS-3E0510HP-E

DS-3E0520HP-E

DS-3E0528HP-E

- L2, Unmanaged, Up to 24 Gigabit RJ45 PoE ports, 2 Gigabit RJ45, 2 Gigabit SFP uplink ports,
- 802.3af/at/bt, Up to 4 port support Hi-PoE 90w, PoE power budget up to 370W, Extend mode support up to 300meter, 6KV surge protection,
- supports POE watchdog, port isolation

NEW



DS-3E0105P-E/M

DS-3E0106P-E/M

DS-3E0109P-E/M

DS-3E0310P-E/M

- L2, Unmanaged, 8 10/100M RJ45 PoE ports, 2 Gigabit RJ45 uplink ports, 802.3af/at,
- PoE power budget 60W, max. 300m long distance transmission, 6KV surge protection

NEW



DS-3E0105P-E

DS-3E0109P-E

DS-3E0318P-E

DS-3E0326P-E

- L2, Unmanaged, 24 10/100M RJ45 PoE ports, 2 Gigabit combo ports, 802.3af/at,
- PoE powerbudget 370W, ports 17 24 support up to 300meter, 6KV surge protection, PoE watchdog, port isolation

NEW



DS-3E0505HP-E

DS-3E0510HP-E

DS-3E0520HP-E

DS-3E0528HP-E

- L2, Unmanaged, 24 Gigabit RJ45 PoE ports, 2 Gigabit RJ45, 2 Gigabit SFP uplink ports, 802.3af/at/bt, port 1 4 support Hi PoE 90w,
- PoE power budget 370W, ports 21 24 support up to 300meter, 6KV surge protection, supports POE watchdog, port isolation



Produk NON-CCTV



NEW
DS-KV8113-WME1

- 2 MP camera with IR supplement
- One nametag button calling design for easier calls
- Built in card reader module
- Standard PoE power supply
- IK08 & IP65 higher protection level with aluminum alloy material
- Convenient Hik Connect APP mobile control



NEW
DS-KH6320-WTE1

- 7" Touch Screen Indoor Station,
- 7 inch Colorful TFT LCD, display resolution: 1024 * 600
- 10/100Mbps Ethernet, Wi Fi 802.11b/g/n
- standard PoE/ 12 VDC.
- TF card, max 32G
- 8 ch alarm input, 2xalarm output, 1x485



NEW
DS-KB8113-IM

- 2MP HD Camera with IR supplement providing excellent image quality
- Supports standard POE power supply
- Supports mechanical doorbell, easier to call
- Convenient Hik Connect APP Mobile Control: Receive calls, open the door and live view remotely
- Supports web configuration
- Higher protection level: IK09 & IP65



DS-KIS702Y

- IP video intercom kit for villa or house, only one call button.
- DS-KD8003-IME2/Surface x 1;
- DS-KH6320-WTE2 x 1;
- DS-KAD704 x 1;
- DS-KAW30-2N x 1;
- 16GB TF card x1;



DS-KIS202 (NEW)

- Analog Kit
- Kit including DS-KB2411-IM and DS-KH2220
- Include one monitor, one outdoor panel, 5-meter 4-wire cable, and other accessories
- you have to mark which standard adapter you want when you place an order



DS-KIS203 (NEW)

- Water Proof Analog Kit
- Kit including DS-KB2421IM and DS-KH2220
- Include one monitor, one metal outdoor panel, 5-meter 4-wire cable, and other accessories
- you have to mark which standard adapter you want when you place an order

DS-KIS604-P

DS-KIS606-P



HOT

- IP video intercom kit for villa or house, only one call button.
- DS-KV8113-WME1 x1;
- DS-KH6320-WTE1 x1;
- 4 port standard PoE switch x1; (for KIS604-S)
- PSU x2;(for KIS604-P)
- 16GB TF card x1;
- No need additional power supply, but you have to mark which standard of power line type of the PoE switch you want when you place an order.(for KIS604-S)
- It includes 2 European power adapters, if you want to change the standard of power supply, you have to mark which standard of power adapter you want when you place an order.(for KIS604-P)